DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 V Frequency: 50/60 H			
Europe and Other Geographies	Voltage: 220-240 V Frequency: 50/60 H			
POWER CONSUMPTION				
Continuous Printing ⁴	565 watts or less			
Ready (Standby) ⁴	46 watts or less			
Energy Saver (Sleep Mode) ⁴	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	0 to 35° C			
Required Temperature Range (Operating)	10 to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels Operating Standby	7.5 B(A) or less 5.3 B(A) or less			
Sound Pressure Levels Operating Standby	56 dB(a) or less 30 dB(a) or less			
Boot Time (from Off to UI Reαdy)	As fast as 60 seconds			
Warm-Up Time (from Sleep to UI Ready)	As fast as 5 seconds	S		
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink B400/DN	459 mm	426 mm	339 mm	14 kg
550-sheet Paper Tray	393 mm	393 mm	94 mm	3.2 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink B400/DN	540 mm	588 mm	480 mm	17.35 kg
550-sheet Paper Tray	498 mm	504 mm	234 mm	4.4 kg
SYSTEM CERTIFICATION/REGUL	ATORY COMPLIANC	E		
Certifications	To view the latest li	st of certifications, go to w	www.xerox.com/Offic	ceCertifications.
PRINT				
First-print-out Time	As fast as 8 seconds	S		
Print Resolution	Up to 1200 x 1200	dpi (enhanced)		
Page Description Languages	PCL [®] 5e, 6 PDF XPS	TIFF JPEG		HP-GL Adobe® PostScript® 3™
Maximum Print Area	4 mm from edge of	f paper		

Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com
Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.

SOFTWARE SOLUTIONS		
Xerox® ConnectKey Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.	
MOBILE SOLUTIONS AND MOBIL	E DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.	
Mopriα [®] Certified	ConnectKey Technology-enabled MFPs are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.	
Xerox [®] @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.	
Xerox [®] Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.	
SECURITY		
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)	

ACCOUNTING				
XEROX® STANDARD AC	COUNTING TOOL / NETWORK A	CCOUNTING (STANDARD)		
Tracking	Print usage			
Accounting	Xerox® Standard Accou Up to 1,000 User Accou Up to 9,999 User Accou Up to 500 General acco Network Accounting (Jo Up to 1,000 User IDs; U	unts without SSD unts with SSD punts)	
		Up to 60,000 Account IDs with SSD ng records (transactions)		
Features	Administrator can man	Administrator can manage the feature via the Embedded Web Server.		
ACCOUNTING OPTION	S – NETWORK ACCOUNTING (AL	LOWS CENTRAL SERVER TO MAN	IAGE ALL ACCOUNTING)	
	 Comprehensive man Numerous solutions of Security enhancemen Device requests accound accounts Accept Authentication 	nts include simultaneous support for	ng and reporting of print usage Partners. For details visit www.xerox.com HTTP/HTTPS protocols server enabling larger databases of users third party Networking Account	
PAPER HANDLING				
BYPASS TRAY				
Capacity ⁵	150 sheets			
Sizes	Custom sizes: 76.2 x 12	7 mm to 216 x 356 mm		
Weights One sided: Two-sided:	60 to 220 gsm 60 to 163 gsm			
Mediα Types	Bond Plain Paper Cardstock Custom	Envelopes Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
TRAY 1	•			
Capacity ⁵	550 sheets			
Sizes	Custom Sizes: 76.2 x 12	Custom Sizes: 76.2 x 127 mm to 216 x 356 mm		
Weights One sided: Two-sided:	60 to 220 gsm 60 to 163 gsm			
Mediα Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
OPTIONAL TRAY 2				
Capacity ⁵	550 sheets			
Sizes	Custom sizes: 139.7 x 2	10 mm to 216 x 356 mm		
Weights One sided: Two-sided:	60 to 220 gsm 60 to 163 gsm			

Media Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
TOTAL CAPACITY ⁵				
Device Standard Capacity ⁵	700 sheets			
Device Total Capacity ⁵	2,350 sheets			
PAPER OUTPUT				
Output Capacity ⁵	250 sheets			
Automatic Two-sided Printing	Standard	Standard		
DEVICE MANAGEMENT				
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® Most protocols not in use can be disabled			
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HT	TPS, TLS, SNTP, MDNS		
REMOTE CONTROL PANEL				
	Enables faster, more conveni IT administrators and other Remote user experience is id-	authorized users can control	the device remotely from a web page	
XEROX® CENTREWARE® WEB				
	management from any work system • Works with any SNMP-mana	station, whether running Wir ged printer from any manufo covery and installations, hea	lth checks and troubleshooting, and	
EMBEDDED WEB SERVER – INTE	GRATED DEVICE WEB PAGE			
Device Status	 Tray status/contents Consumables status Billing / Usage Quick Links Online Support 			
Print Queue Viewing	Job print queue management-	-view and delete		
Job Submission	Print-ready files (PS, PCL, PDF,)	(PS, JPEG)		
Device Administration	Allows simple, remote installati	on setting of configuration o	options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™			

Xerox® VersaLink® B400 Printer

REMOTE SERVICES		
Automated Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automated Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
WHAT COMES IN THE BOX		
	VersaLink B400 Printer Standard Capacity Toner Cartridge: 5,900 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recand Warranty Statement) Installation Guide Quick Use Guides Power cord	ycling and Disposal Guides, Print Drivers,
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	5,900 standard pages ⁶	106R03580
High Capacity Toner Cartridges	13,900 standard pages ⁶	106R03582
High Capacity Toner Cartridges Extra-High Capacity Toner Cartridges	13,900 standard pages ⁶ 24,600 standard pages ⁶	106R03582 106R03584
Extra-High Capacity		
Extra-High Capacity Toner Cartridges	24,600 standard pages ⁶	106R03584
Extra-High Capacity Toner Cartridges Drum Cartridge	24,600 standard pages ⁶	106R03584
Extra-High Capacity Toner Cartridges Drum Cartridge ACCESSORIES / OPTIONS	24,600 standard pages ⁶ 65,000 standard pages ⁷	106R03584 101R00554
Extra-High Capacity Toner Cartridges Drum Cartridge ACCESSORIES / OPTIONS 550-sheet Paper Tray	24,600 standard pages ⁶ 65,000 standard pages ⁷	106R03584 101R00554 497K13620

¹ Declared print speed in accordance with ISO/IEC 24734.

For more information, visit us at www.xerox.com/Office

Configurations vary by geography.

Declared print speed in accordance with ISO/IEC 24/34.

2 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

3 Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

4 Power states defined per ENERGY STARs Program requirements for Imaging Equipment.

5 Paper capacities are based on 20 lb. 75 gam stock; capacities will vary with different weight stocks.

6 Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

7 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.